

ECONOLITE

ACRYLIC DOMED SKYLIGHTS FOR ALL ROOF TYPES—TILE, CGI DECK & SLATE



FEATURES

- Self-cleaning, high-density, UV stabilised 'Opal' acrylic dome
- Base and Flashing assembly in Zinalume as Standard. Galvanised Iron or Colourbond finishes, available on request
- Manufactured and tested to meet Australian Standard AS4285-Skylights

<p>HIA-SIA SKYLIGHT INDUSTRY ASSOCIATION SIA APPROVAL NUMBER 007</p>	1200 Negative	Pa	<p>ATLITE</p>
	670 Positive		

AS4285-Skylights-Proof of test label

STANDARD SIZE RANGE		
Inside Size (mm)	Light Area (m ²)	Clear Ventilation (m ²)
500 x 500	0.250	0.078
600 x 600	0.360	0.092
800 x 500	0.400	0.099
800 x 600	0.480	0.105
1200 x 500	0.600	0.126
800 x 800	0.640	0.119
1200 x 600	0.720	0.133
900 x 900	0.810	0.133
1200 x 800	0.960	0.146
1000 x 1000	1.000	0.146
1200 x 1200	1.440	0.173
1500 x 1500	2.250	0.214

Note: When ordering also specify size, roof type and venting requirements. When ordering rectangular units, it must be specified which way the longer side runs to determine whether the skylight runs in a vertical or horizontal position on the roof.

Other sizes available upon request.



AVAILABLE FROM

Atlite Skylites

27 Kembla Road Cheltenham 3192
Tel: (03) 9584 8500 Fax: (03) 9585 0781
E-mail: skylite@atlite.com.au
Internet: <http://www.atlite.com.au>

